



Intelligent Features and TECHNOLOGY

Model WF-5220 - Output: 120V AC - Pure Sine Wave, 60 Hz, 2000W Input: 10-15 V DC

Reliability. Vertically integrated, WFCO has total supply chain control, ensuring quality materials, parts and processes at each stage. Components are quality tested at critical manufacturing stages resulting in zero faults at the final 4-hour burn-in test, helping keep warranty claims below 1%. All models are UL® and cUL® listed and FCC Class B compliant.

WFCO's 2000-watt WF-5220 Inverter Series delivers outstanding performance. The internal transfer system automatically allows the AC input to bypass the inverter when the inverter is connected to an AC power source. Other essential features include pure sine wave output, providing the hi-tech filtering needed for premium electronics and refrigerators, plus an easy hi-pot testing design that allows hi-potting output circuits through the inverter.

With over a decade of inverter manufacturing, WFCO knows what is essential. Reliability, clean signal, easy installation, and intelligent power management make the WF-5220 Inverter Series the best choice in RV inverters.

PRODUCT FEATURES

REMOTE DISPLAY PANEL

The included LED/LCD display provides status indication as well as inverter readings.

LED DISPLAY

- **Blue** - Indicates unit is on and normal
- **Red** - Indicates error status

LCD SCREEN

- DC voltage
- Inverter temperature
- Grid input voltage, amperage, frequency and watts
- Inverter output voltage, amperage, frequency, and watts
- Fault codes
- Inverter settings

ADDITIONAL SERIES FEATURES

- 30A Pass-Thru with AC Auto-Reset Fuse
- Programmable over/under DC voltage protection
- Reverse Polarity with Light Indicator
- High-frequency switching mode power topology for a smaller, lighter, quieter and more-efficient unit.
- THD < 3% ; Pure Sine Wave output waveform supplies you with higher quality power than the electric company provides.
- Convenient WAGO AC Hookup
- Mount in Any Position
- Brushless fans
- Automatic transfer switch with 100% default to utility power.



The WF-5220 Inverter remote includes an LCD display and a 32-ft cable. Display includes On/Off button, Battery Voltage status, Grid Input Voltage and Amperage status and settings for Battery Under (UVP) and Over (OVP) Voltage Protection.



A remote cable comes standard for all WF-5220 models and is designed for ease of installation.

SPECIFICATIONS	WF-5220
Power Output	2000 W
Input Voltage	10-15 V DC
Output Waveform	Pure Sine Wave
Voltage Output	120 V AC / 60 Hz
Efficiency Load	>88%
Transfer Switch Rating	30 A
Transfer Time	<20 milliseconds
AC Output Circuit Breaker	30 A
Dimensions	8"W x 14 3/8"L x 4"H
Weight	20 lb

Certifications: UL® and cUL® listed and FCC Class B compliant. Specifications are subject to change without notice or obligation.

ALL MODELS STANDARD SAFETY FEATURES PROTECTIONS

Overload, Short Circuit, Over/Under Input Voltage, Over Temperature, AC Output Circuit Breaker, Battery Input Reverse Polarity Protection



EXPERT PRODUCT SUPPORT

Our Power Pros provide expert technical support for everything the RV industry needs. Visit wfcoelectronics.com/support.